

Appl. No. 10/627,615
Amdt. Dated April 4, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listing, of claims in the application:

Listing of Claims:

1. (Previously Amended): A sensor array forming part of an intrusion detection system and having a plurality of discrete volumetric sensors each having an associated volumetric intrusion detection field extending therefrom and constructed and arranged to generate a response to an intruder entering its detection field, the sensor array comprising:

a plurality of sensor nodes each having at least one volumetric sensor and having a detection zone defined by the effective detection fields of its constituent sensors as constructed and arranged in each sensor node, at least one of the sensor nodes having at least two volumetric sensors; and

an array processor coupled to each sensor node for generating information based on processing of the response generated from the detection zone of each sensor node.

2. (Cancelled):

3. (Cancelled):

4. (Previously Amended): The sensor array according to claim 1, wherein each discrete volumetric sensor is selected from at least one member of the group consisting of: microwave modules, ultrasonic transducers, passive IR sensors, and active reflective IR sensors.

Appl. No. 10/627,615
Amdt. Dated April 4, 2005

5. (Previously Amended): The sensor array according to claim 1, wherein the sensor array includes a distribution point for connecting a means for providing power, the distribution point being coupled to the array processor and each sensor node.
6. (Previously Amended): The sensor array according to claim 1, wherein each sensor node is encased within and spaced along a deformable cable.
7. (Previously Amended): The sensor array according to claim 1, wherein the sensor array is encased within an elongated housing.
8. (Previously Amended): The sensor array according to claim 1, wherein each sensor node is formed as an integrated circuit.
9. (Previously Amended): The sensor array according to claim 1, wherein at least two of the detection zones overlap.
10. (Previously Amended): The sensor array according to claim 1, wherein at least two of the detection zones abut.
11. (Cancelled):
12. (Previously Amended): The sensor array according to claim 1, wherein adjacent sensor nodes of the plurality of sensor nodes are spaced apart along the sensor array, and wherein the space between adjacent sensor nodes has a predetermined range based upon a span of each detection zone.
13. (Previously Amended): The sensor array according to claim 1, wherein adjacent sensor nodes of the plurality of sensor nodes are spaced apart along the sensor array, and

Appl. No. 10/627,615
Amdt. Dated April 4, 2005

wherein the space between adjacent sensor nodes has a predetermined range based upon a distance to be detected.

14. (Previously Amended): The sensor array according to claim 1, wherein adjacent sensor nodes of the plurality of sensor nodes are spaced apart along the sensor array, and wherein the space between adjacent sensor nodes has a range of 0.25-20.0 meters.

15. (Currently Amended): A sensor array forming part of an intrusion detection system and having a plurality of discrete volumetric sensors each having an associated volumetric intrusion detection field extending therefrom and constructed and arranged to generate a response to an intruder entering its detection field, the sensor array comprising:

- (i) a plurality of sensor nodes each sensor node having at least one volumetric sensor and having a detection zone defined by the effective detection fields of its constituent sensors as constructed and arranged in each sensor node, at least one of the sensor nodes having at least two volumetric sensors, and each sensor node having a node processor for generating an alarm disturbance signature based on the response generated by each volumetric sensor of the sensor node, the node processor being coupled to each volumetric sensor; and
- (ii) an array processor for generating information based on the alarm disturbance signature received from each node processor, the array processor being coupled to the node processor of each sensor node.

16. (Cancelled):

17. (Previously Amended): The sensor array according to claim 15, wherein each discrete volumetric sensor is selected from at least one member of the group consisting

Appl. No. 10/627,615
Amdt. Dated April 4, 2005

of: microwave modules, ultrasonic transducers, passive IR sensors, and active reflective IR sensors.

18. (Previously Amended): An intrusion detection system comprising:

(I) at least one sensor array having a plurality of discrete volumetric sensors each having an associated volumetric intrusion detection field extending therefrom and constructed and arranged to generate a response to an intruder entering its detection field, the system having:

(i) a plurality of sensor nodes each sensor node having at least one volumetric sensor and having a detection zone defined by the effective detection fields of its constituent sensors as constructed and arranged in each sensor node, at least one of the sensor nodes having at least two volumetric sensors, and each sensor node having a node processor for generating an alarm disturbance signature based on the response generated each volumetric sensor of the sensor node, the node processor being coupled to each volumetric sensor; and

(ii) an array processor for generating information based on the alarm disturbance signature received from each node processor, the array processor being coupled to the node processor of each sensor node;

(II) a calibration means for adjusting the sensitivity setting of each discrete sensor; and

(III) a system processor for processing the information received from the array processor and for generating an alarm condition;

wherein the calibrating system is coupled to the system controller, and wherein the system controller is coupled to each sensor array.

19. (Cancelled):

Appl. No. 10/627,615
Amdt. Dated April 4, 2005

20. (Previously Amended): An intrusion detection system according to claim 18, wherein each discrete volumetric sensor is selected from at least one member of the group consisting of microwave modules, ultrasonic transducers, passive IR sensors, and active reflective IR sensors.
21. (Previously Added): The sensor array according to claim 1, wherein adjacent sensor nodes are spaced apart based on at least one criterion selected from the group consisting of: discrete sensor phenomenology, discrete sensor detection features, intruder type, intruder orientation, detection zones of the adjacent sensor node, and range of detection zones of the adjacent sensor nodes.
22. (Previously Added): The sensor array according to claim 15, wherein adjacent sensor nodes are spaced apart based on at least one criterion selected from the group consisting of: discrete sensor phenomenology, discrete sensor detection features, intruder type, intruder orientation, detection zones of the adjacent sensor node, and range of detection zones of the adjacent sensor nodes.
23. (Previously Added): The intrusion detection system according to claim 18, wherein adjacent sensor nodes are spaced apart based on at least one criterion selected from the group consisting of: discrete sensor phenomenology, discrete sensor detection features, intruder type, intruder orientation, detection zones of the adjacent sensor node, and range of detection zones of the adjacent sensor nodes.
24. (Previously Added): The sensor array according to claim 1, wherein at least one of the sensor nodes has a discrete non-volumetric sensor.
25. (Previously Added): The sensor array according to claim 15, wherein at least one of the sensor nodes has a discrete non-volumetric sensor.

Appl. No. 10/627,615
Amdt. Dated April 4, 2005

26. (Previously Added): The sensor array according to claim 18, wherein at least one the sensor nodes having has a discrete non-volumetric sensor.